

Specifications

Product Codes	MF28VN: natural gas / MF28VP: propane
Product type	Direct Vent, Freestanding.
Input (BTU)	Natural gas: 26,000 / 15,500 Propane: 24,000 / 15,200
Vent Outlet	4 x 6-5/8" co-axial. Top or Rear outlet.
Venting System	Co-axial 4 x 6-5/8". Co-axial flex 3x5. Top outlet: Minimum 24" vertical rise before elbow. Rear outlet: Maximum horizontal without rise: 24", then snorkel minimum 36" high.
Gas convertible	Yes
Valve	GV60
Control	ValorPLUS remote control. Optional Remote Battery & Wall Switch Kit or Wall Switch Kit.
Batteries	Fireplace: Yes, in battery box; Remote control handset: Yes Optional Remote Battery & Wall Switch Kit
Electrical	Optional, to operate optional fan.
Lighting	No
Wifi	No
Fan (Blower)	¹ Optional. Operated by speed control box or hardwired with wall control. No remote.
HeatShift	No
Liners	No
Fuel beds	V-Logs: Traditional, Driftwood, Birch.
Fronts / Trims	Traditional or Modern stove casings. Choice of colors. NEW screen for black option.
Outdoor Installation	No
Comments	¹ Fan operates independently from remote control.