

Specifications

Product Codes	200AN: natural gas / 200AP: propane
Product type	Direct Vent, Zero clearance
Input (BTU)	NG 20,000 / 9,500 Propane 20,000 / 10,000
Vent Outlet Take-Off	4 x 6-5/8" co-axial, orientation top or rear
Venting System	Co-axial 4 x 6-5/8"; Co-Linear 3x3 w/1156CLA; Co-Linear wall termination 720SWK; Co-axial flex 5x3 w/590CFA + 590FVK2
Gas convertible	Yes
Valve	GV60
Remote Control	Valor10 remote control
Batteries	Fireplace: Yes, 4 x AA, in battery box; Remote control handset: Yes, 2 x AAA
Electrical	Optional, via v-module to operate optional fan, optional WiFi.
Lighting	No
WiFi	Optional. If no fan installed, needs V-module GV60VM + Electrical box P2-WPK
Fan (Blower)	Optional, 255CFK
HeatShift	Optional, LDK12—Plenum 2 ports 4" dia., LDK9—4" dia. liners; LDK13—Finishing plate
Liners	Plain black, Charcoal Bricks, Reflective Glass
Fuel beds	Birch, Driftwood, Traditional
Fronts / Backing Plate	Fronts: CIK / 4-sided Ledgeview / Clearview (needs BP). Backing Plates: width 26", 36" and 26" reduced depth.
Outdoor Installation	Yes, no electrical connection allowed. Requires GV60CKO Outdoor Conversion kit.
Comments	